

UK DS Subscriber drop



Indoor drop cable



Product Description

Subscriber drop cable for indoor use

Features

- Discreet design: compact diameter (<3mm), colour of the sheath (ivory)
- Fire protected sheath LSOH-FR (Low Smoke Zero Halogen- Flame Retardant, complies to CPR (see table for classification)
- Lightweight
- Can be glued to surfaces
- Option to pre-terminate ends

Technical Specification

		Series 1210 (1 fibre)	Series 1211 (2 fibres)
Nominal outer diameter (mm)		2.8	3
Nominal thickness of sheath (mm)		0.5	
Tensile strength (N)		150	
Maximum crush resistance (N/10cm)		100	
Minimum bend radius (mm)		20	
Nominal weight (kg/km)		8	9
Temperature	Storage and transport	-40 / +70°C	
	Installation	-5 / +50°C	
	Operation	-5 / +70°C	
Standard packaging		Coil of 250m	
CPR Euroclasse		D _{ca} -s2, d2, a2	
Storage		indoor	

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emteille can take no responsibility for actions taken based on the information contained in this document. Emteille reserves the right to make changes to this document without notice. All sales of product are subject to Emteille's terms and conditions of sale only, which can be found on Emteille's website.

This document is protected by copyright (c) Emteille UK Limited [2019]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emteille UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emteille.com