

EF450-017

Issue Number: 7

Page 1 of 2



uPVC Duct - Telecoms

Product Description

Emtelle uPVC Telecoms Duct is designed, manufactured, and supplied within an Integrated Management System, incorporating internationally recognised Standards including ISO 9001:2015, ISO 14001:2015 and ISO 45001:2018.




Application

The duct is designed to comply with BS EN 61386 (formerly BS EN 50086-2-4) Industry Standard (450N class).

uPVC Telecom duct is available with 2 socket types: Standard interference Socket (IP4X), and also Emtelle's innovative new Interference Ring Seal (IRS) Socket (IP68). Additional information on this new socket can be found in specification EF450-019.

Duct systems are printed with standard markings, including any additional information required by the customer, to give durability and traceability after installation.





Material & Technical data

Raw Materials are uPVC resin and other additives suitable for the required properties of the finished product.

Colours

Colour fastness and UV stability for UK and Ireland only, for 6 months external storage unless otherwise agreed by customer specification.

Standard colours are Grey, Green & Purple.

Other colours available upon request.

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website

This document is protected by copyright (c) Emtelle Group [2021]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com



EF450-017

Issue Number: 7

Page 2 of 2

Standard Dimensions & Product Codes

Nominal OD / ID	Class	Length	Colour	Interference Fit Socket	Interference Ring Seal Socket	Lengths per pallet
53.9 / 50mm	450N	3m	Grey	1562	-	370
			Green	163L	-	
	450N	6m	Grey	5636	-	
			Green	20425	-	
63 / 59mm	450N	6m	Grey	✓		288
			Green	20364	-	
			Purple	20292	-	
88.9 / 83mm	450N	6m	Grey	20385	-	138
			Green	✓	-	
			Purple	✓	-	
96.5 / 90mm	450N	3m	Grey	✓	-	115
			Green	20554	-	
	450N	6m	Grey	857L	-	
			Green	1879L	-	
			Purple	20812	-	
110 / 103mm	450N	6m	Grey	5701	√	90
			Green	20246	20362	
			Purple	20293	√	
125 / 118mm	450N	6m	Grey	✓	√	68
			Green	20095	√	
			Purple	√	21008	
160 / 151mm	450N	6m	Grey	20500	√	39
			Green	20536	20592	
			Purple	20891	21298	

Packaging and Labelling

All products suitably packaged in recyclable materials and clearly labelled with Emtelle Product Code and Description where possible.

The duct is supplied on non-returnable wooden U-frames which are designed to be stored on even, stable ground; they must not be stored more than 3 high. Packaging should be recycled locally.

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website

website.

This document is protected by copyright (c) Emtelle Group [2021]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com