

 FibreFlow  PowerProtect+TM
Access Chamber - CUBIS
(STAKKAboxTM Fortress)

Product Description

STAKKAbox FORTRESS is a range of sectional, modular and structural preformed access chamber. Each chamber is made from 150mm stacking sections which interlock to offer flexibility in finished chamber depths.

Application

Supplied in 150mm deep twinwall rings, the system provides contractors with a means of constructing access chambers quickly and inexpensively, whilst offering improved build quality, reduced defects and enhanced site safety performance.

Built by stacking sections to required depth, each part weighs under 25kg, making it suitable for a single person to lift under manual handling guidelines.

The product is designed for both footway and roadway installations where it provides access to underground ducting (EN124 Class A15 to D400)

Colour is Black

Working Temperature range -40°C to +100°C



Design Features

- Fast & Easy to install
- Sections & Twill Walled Design
- Single person lifting
- No Specialist Tools Required
- Smooth Outer Walls with Lip to 'Key In'

Material & Technical data

STAKKAboxTM Fortress is manufactured in nitrogen-foamed High Density Polyethylene (HDPE), of which up to 70% is recycled material.

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website.

This document is protected by copyright (c) Emtelle Group [2021]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com

Testing & Standards

Fortress access chambers are suitable for installation in environments rated to D400 under EN124.

Standard Dimensions, Colours & Product Codes

Code	Ref	Length	Width	Depth	Cover Weight	Rings / Pallet
71889	FW1/EN1	600mm	450mm	150mm	5.56kg	40
71890	FW2/EN2	725mm	255mm	150mm	6.16kg	40
71730	FW4/EN4	915mm	445mm	150mm	7.04kg	32
71891*	FW6/EN6	1,310mm	610mm	150mm	16.84kg	30

* Is a different profile, suitable to take vertical loading up to 60tonnes.

Packaging and Labelling

All products suitably packaged in recyclable materials and clearly labelled with Emtelle Product Code and description where possible. Access Chambers are supplied on timber pallets. The pallets are designed to be stored on an even, dry, and stable area.

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website.

This document is protected by copyright (c) Emtelle Group [2021]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com