

## UK DS 71503



### External Customer Lead in Kit (Large)



#### Product Description

The external customer lead-in kit (large) has been designed to house a drop duct (up to 54mm diameter) exiting from the ground, to a position on a vertical wall where fibre is required to penetrate into the building. This system can be used to house both copper and fibre cables as well as blown fibre single tubing up to a diameter of 5mm. This can be cut to length to fit most entries from 32cm above ground to 82cm above ground.

#### Kit Components

The kit comprises of the following components:



Lead in Top P/C 74339
1 x External CLI Cover
1 x External CLI Base
4 x Screws



Capping 25A P/C 73807
1 x Capping 25A
4 x Screws



Bend No.4 P/C 73806
1 x Connector Bend
4 x Screws

For more information on these items see the relevant UK\_DS

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website.

This document is protected by copyright (c) Emtelle UK Limited [2019]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

[www.emtelle.com](http://www.emtelle.com)