

UK_DS_7217



Indoor Tube Flexibility Point (ITFP) 4 Port



Design Features

- Manufactured from UL94, V0 rated material.
- IP55 Rated.
- Can accommodate 5mm FibreFlow tube bundles up to 19way.
- Can be used as a straight joint or drop joint.
- Provision of secure long term bend protection.
- Can be retrofitted.
- Re-enterable.
- Can be readily fixed to walls or inside a cable tray.
- Easy to use and install, no special tools required.



Application

The FibreFlow Indoor Tube Flexibility Point (ITFP) is a branch box capable of manipulating a 19 way tube bundle and routing any combination of tube bundles to four separate ports. Each port is identifiable by means of a recessed name-plate.

Technical Specification

Materials: UL94, V0 rated Plastic

Dimensions:

Length 520 mm (20.5") Width 280 mm (11") Depth 70 mm (2.8")

Installation Instructions

See UK_II_7217 (check with Emtelle for most recent issue).

End of Specification

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.