



Tube Distribution Closure (TDC) Product Code 7514



(not all items in diagram included)

Design Features

- Accepts fibreflow™ tube bundles and sub ducts up to 40mm (1.6") in diameter
- One piece grommet and seal arrangement
- Manifold option allows 6 x 1DB to be dropped off from 1 port (shown above P/C:7717)
- Captivated screws in lid portion allowing inverted installation
- Can be re-entered
- Can be retro-fitted to existing tube bundles/sub ducts
- Straight through, H, Y and T configurations possible
- IP40 rated
- Lightweight - 1.2Kg (2.6lb)

Application

Tube Distribution Closure (TDC) can be Direct Buried into a waiting trench (following DB fibreflow installation procedures on back-fill) or placed inside a manhole or handhole. Adaptor kits are available:

| Description | Emtelle Product Code |
|----------------------------|----------------------|
| 7- way DB 5mm adaptor kit | 9111 |
| 12 -way DI 5mm adaptor kit | 9111 |
| 12-way DB 5mm adaptor kit | 9112 |
| 19-way DB 5mm adaptor kit | 9113 |
| 24-way DB 3mm adaptor kit | 9115 |

*7DB/12DI adaptors are the same.

Material & Technical data

| | |
|-------------|---|
| Materials: | Plastic shell. All metallic parts Stainless Steel |
| Dimensions: | Length: 316mm (12.4") Width: 220mm (8.7") Height: 70mm (2.8") |
| Colours: | All plastic parts Black Grommets & seal Black |

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website.

This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com

UK DS 7514

Issue D: 13/04/2020

Page 2 of 2

| | |
|---------------------|--|
| Impact: | 1Kg (2.2lbs) weight dropped from 1m (3.3 feet) |
| Ingress Protection: | IP40 |
| Pull out: | Drop Port: >940N (>211lbf) |
| | Other Ports: >1340N (>301lbf) |

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website.

This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

www.emtelle.com